




Features

- ◆ Silicon Planar Zener Diodes
- ◆ In MiniMELF case especially for automatic insertion
- ◆ The Zener voltages are graded according to the international E 24 standard. Offered with either 5% or 2% tolerance. Smaller voltage tolerances and other Zener voltages are available upon request.
- ◆ These diodes are also available in DO-35 case with the type designation ZPD1 ... ZPD51

Mechanical Data

- ◆ Case: MiniMELF Glass Case (SOD-80)
- ◆ Weight: approx. 0.05g



Maximum Ratings and Thermal Characteristics

($T_A=25^\circ\text{C}$ unless otherwise noted)

| Parameter | Symbol | Value | Unit |
|--|-----------------------|--------------------|--------------------|
| Zener current (see Table "Characteristics") | | | |
| Power dissipation at $T_{\text{amb}}=25^\circ\text{C}$ | P_{tot} | 500 ⁽¹⁾ | mW |
| Thermal resistance junction to ambient air | $R_{\theta\text{JA}}$ | 300 ⁽¹⁾ | $^\circ\text{C/W}$ |
| Junction temperature | T_J | 175 | $^\circ\text{C}$ |
| Storage temperature range | T_S | -55 to +175 | $^\circ\text{C}$ |

Notes: 1. Valid provided that electrodes are kept at ambient temperature.

Electrical Characteristics

(T_A=25°C unless otherwise noted)

| Type number add suffix B for ±2% tol. | Dynamic resistance | | Temp. coefficient of zener voltage at I _Z =5mA α _{VZ} (10 ⁻⁴ / °C) | | Maximum reverse leakage current | | Admissible zener current ⁽²⁾ | |
|---|---|---|--|------|---------------------------------|------------------------------|---|---|
| | at I _Z =5mA f=1kHz r _{Zj} (Ω) | at I _Z =1mA f=1kHz r _{Zj} (Ω) | Min. | Max. | I _R (μA) | at V _R (Volts) | at T _{amb} =45°C I _Z (mA) | at T _{amb} =25°C I _Z (mA) |
| ZMM1 ⁽³⁾ | 6.5 (< 8) | < 50 | -26 | -23 | - | - | 280 | 340 |
| ZMM2.4 | <100 | <600 | -10 | -5 | 50 | 0.8 | 152 | 175 |
| ZMM2.7 | 75 (< 83) | < 500 | -9 | -4 | 20 | 0.8 | 135 | 160 |
| ZMM3 | 80 (< 95) | < 500 | -9 | -3 | 20 | 0.8 | 117 | 140 |
| ZMM3.3 | 80 (< 95) | < 500 | -8 | -3 | 6 | 0.8 | 109 | 130 |
| ZMM3.6 | 80 (< 95) | < 500 | -8 | -3 | 6 | 0.8 | 101 | 120 |
| ZMM3.9 | 80 (< 95) | < 500 | -7 | -3 | 1.6 | 0.8 | 92 | 110 |
| ZMM4.3 | 80 (< 95) | < 500 | -6 | -1 | 1.0 | 0.8 | 85 | 100 |
| ZMM4.7 | 70 (< 78) | < 500 | -5 | +2 | 0.1 | 0.8 | 76 | 90 |
| ZMM5.1 | 30 (< 60) | < 480 | -3 | +4 | 0.1 | 0.8 | 67 | 80 |
| ZMM5.6 | 10 (< 40) | < 400 | -2 | +6 | 0.1 | 1 | 59 | 70 |
| ZMM6.2 | 4.8 (< 10) | < 200 | -1 | +7 | 0.1 | 2 | 54 | 64 |
| ZMM6.8 | 4.5 (< 8) | < 150 | +2 | +7 | 0.1 | 3 | 49 | 58 |
| ZMM7.5 | 4 (< 7) | < 50 | +3 | +7 | 0.1 | 5 | 44 | 53 |
| ZMM8.2 | 4.5 (< 7) | < 50 | +4 | +7 | 0.1 | 6 | 40 | 47 |
| ZMM9.1 | 4.8 (< 10) | < 50 | +5 | +8 | 0.1 | 7 | 36 | 43 |
| ZMM10 | 5.2 (< 15) | < 70 | +5 | +8 | 0.1 | 7.5 | 33 | 40 |
| ZMM11 | 6 (< 20) | < 70 | +5 | +9 | 0.1 | 8.5 | 30 | 36 |
| ZMM12 | 7 (< 20) | < 90 | +6 | +9 | 0.1 | 9 | 28 | 32 |
| ZMM13 | 9 (< 25) | < 110 | +7 | +9 | 0.1 | 10 | 25 | 29 |
| ZMM15 | 11 (< 30) | < 110 | +7 | +9 | 0.1 | 11 | 23 | 27 |
| ZMM16 | 13 (< 40) | < 170 | +8 | +9.5 | 0.1 | 12 | 20 | 24 |
| ZMM18 | 18 (< 50) | < 170 | +8 | +9.5 | 0.1 | 14 | 18 | 21 |
| ZMM20 | 20 (< 50) | < 220 | +8 | +10 | 0.1 | 15 | 17 | 20 |
| ZMM22 | 25 (< 55) | < 220 | +8 | +10 | 0.1 | 17 | 16 | 18 |
| ZMM24 | 28 (< 80) | < 220 | +8 | +10 | 0.1 | 18 | 13 | 16 |
| ZMM27 | 30 (< 80) | < 250 | +8 | +10 | 0.1 | 20 | 12 | 14 |
| ZMM30 | 35 (< 80) | < 250 | +8 | +10 | 0.1 | 22.5 | 10 | 13 |
| ZMM33 | 40 (< 80) | < 250 | +8 | +10 | 0.1 | 25 | 9 | 12 |
| ZMM36 | 40 (< 90) | < 250 | +8 | +10 | 0.1 | 27 | 9 | 11 |
| ZMM39 | 50 (< 90) | < 300 | +10 | +12 | 0.1 | 29 | 8 | 10 |
| ZMM43 | 60 (< 100) | < 700 | +10 | +12 | 0.1 | 32 | 7 | 9.2 |
| ZMM47 | 70 (< 100) | < 750 | +10 | +12 | 0.1 | 35 | 6 | 8.5 |
| ZMM51 | 70 (< 100) | < 750 | +10 | +12 | 0.1 | 38 | 6 | 7.8 |
| ZMM56 | < 135 ⁽⁴⁾ | < 1000 ⁽⁵⁾ | typ. +10 ⁽⁴⁾ | - | 0.1 | 42 | 5.2 | 7.1 |
| ZMM62 | < 150 ⁽⁴⁾ | < 1000 ⁽⁵⁾ | typ. +10 ⁽⁴⁾ | - | 0.1 | 47 | 4.8 | 6.4 |
| ZMM68 | < 200 ⁽⁴⁾ | < 1000 ⁽⁵⁾ | typ. +10 ⁽⁴⁾ | - | 0.1 | 51 | 4.1 | 5.8 |
| ZMM75 | < 250 ⁽⁴⁾ | < 1500 ⁽⁵⁾ | typ. +10 ⁽⁴⁾ | - | 0.1 | 55 | 3.9 | 5.3 |

- Notes:**
1. Tested with pulses t_p=5ms
 2. Valid provided that electrodes are kept at ambient temperature
 3. The ZMM1 is a silicon diode operated in forward direction Hence, the index of all parameters should be "F" instead of "Z" Connect the cathode electrode to the negative pole
 4. at I_Z=2.5mA
 5. at I_Z=0.5mA

Electrical Characteristics

(T_a=25°C unless otherwise noted)

| Type number ±5% Tol. | Zener voltage range ⁽¹⁾ at I _Z V _Z (Volts) | | Test current I _Z (mA) |
|-------------------------|--|------|-------------------------------------|
| | Min. | Max. | |
| ZMM1 ⁽²⁾ | 0.70 | 0.80 | 5.0 |
| ZMM2.4 | 2.20 | 2.60 | 5.0 |
| ZMM2.7 | 2.50 | 2.90 | 5.0 |
| ZMM3 | 2.80 | 3.20 | 5.0 |
| ZMM3.3 | 3.10 | 3.50 | 5.0 |
| ZMM3.6 | 3.40 | 3.80 | 5.0 |
| ZMM3.9 | 3.70 | 4.10 | 5.0 |
| ZMM4.3 | 4.00 | 4.60 | 5.0 |
| ZMM4.7 | 4.40 | 5.00 | 5.0 |
| ZMM5.1 | 4.80 | 5.40 | 5.0 |
| ZMM5.6 | 5.20 | 6.00 | 5.0 |
| ZMM6.2 | 5.80 | 6.60 | 5.0 |
| ZMM6.8 | 6.40 | 7.20 | 5.0 |
| ZMM7.5 | 7.00 | 7.90 | 5.0 |
| ZMM8.2 | 7.70 | 8.70 | 5.0 |
| ZMM9.1 | 8.50 | 9.60 | 5.0 |
| ZMM10 | 9.40 | 10.6 | 5.0 |
| ZMM11 | 10.4 | 11.6 | 5.0 |
| ZMM12 | 11.4 | 12.7 | 5.0 |
| ZMM13 | 12.4 | 14.1 | 5.0 |
| ZMM15 | 13.8 | 15.6 | 5.0 |
| ZMM16 | 15.3 | 17.1 | 5.0 |
| ZMM18 | 16.8 | 19.1 | 5.0 |
| ZMM20 | 18.8 | 21.2 | 5.0 |
| ZMM22 | 20.8 | 23.3 | 5.0 |
| ZMM24 | 22.8 | 25.6 | 5.0 |
| ZMM27 | 25.1 | 28.9 | 5.0 |
| ZMM30 | 28.0 | 32.0 | 5.0 |
| ZMM33 | 31.0 | 35.0 | 5.0 |
| ZMM36 | 34.0 | 38.0 | 5.0 |
| ZMM39 | 37.0 | 41.0 | 5.0 |
| ZMM43 | 40.0 | 46.0 | 5.0 |
| ZMM47 | 44.0 | 50.0 | 5.0 |
| ZMM51 | 48.0 | 54.0 | 5.0 |
| ZMM56 | 52.0 | 60.0 | 2.5 |
| ZMM62 | 58.0 | 66.0 | 2.5 |
| ZMM68 | 64.0 | 72.0 | 2.5 |
| ZMM75 | 70.0 | 79.0 | 2.5 |

| Type number add suffix B ±2% Tol. | Zener voltage range ⁽¹⁾ at I _Z V _Z (Volts) | | Test current I _Z (mA) |
|---|--|------|-------------------------------------|
| | Min. | Max. | |
| ZMM1 ⁽²⁾ | - | - | - |
| ZMM2.4 | - | - | - |
| ZMM2.7 | 2.65 | 2.75 | 5.0 |
| ZMM3 | 2.94 | 3.06 | 5.0 |
| ZMM3.3 | 3.23 | 3.37 | 5.0 |
| ZMM3.6 | 3.53 | 3.67 | 5.0 |
| ZMM3.9 | 3.82 | 3.98 | 5.0 |
| ZMM4.3 | 4.21 | 4.39 | 5.0 |
| ZMM4.7 | 4.61 | 4.79 | 5.0 |
| ZMM5.1 | 5.00 | 5.20 | 5.0 |
| ZMM5.6 | 5.49 | 5.71 | 5.0 |
| ZMM6.2 | 6.08 | 6.32 | 5.0 |
| ZMM6.8 | 6.66 | 6.94 | 5.0 |
| ZMM7.5 | 7.35 | 7.65 | 5.0 |
| ZMM8.2 | 8.04 | 8.36 | 5.0 |
| ZMM9.1 | 8.92 | 9.28 | 5.0 |
| ZMM10 | 9.80 | 10.2 | 5.0 |
| ZMM11 | 10.8 | 11.2 | 5.0 |
| ZMM12 | 11.8 | 12.2 | 5.0 |
| ZMM13 | 12.7 | 13.3 | 5.0 |
| ZMM15 | 14.7 | 15.3 | 5.0 |
| ZMM16 | 15.7 | 16.3 | 5.0 |
| ZMM18 | 17.6 | 18.4 | 5.0 |
| ZMM20 | 19.6 | 20.4 | 5.0 |
| ZMM22 | 21.6 | 22.4 | 5.0 |
| ZMM24 | 23.5 | 24.5 | 5.0 |
| ZMM27 | 26.5 | 27.5 | 5.0 |
| ZMM30 | 29.4 | 30.6 | 5.0 |
| ZMM33 | 32.3 | 33.7 | 5.0 |
| ZMM36 | 35.3 | 36.7 | 5.0 |
| ZMM39 | 38.2 | 39.8 | 5.0 |
| ZMM43 | 42.1 | 43.9 | 5.0 |
| ZMM47 | 46.1 | 47.9 | 5.0 |
| ZMM51 | 50.0 | 52.0 | 5.0 |
| ZMM56 | 54.9 | 57.1 | 2.5 |
| ZMM62 | 60.8 | 63.2 | 2.5 |
| ZMM68 | 66.6 | 69.4 | 2.5 |
| ZMM75 | 73.5 | 76.5 | 2.5 |


- Notes:**
1. Measured with pulses t_p=5 ms
 2. The ZMM1 is a silicon diode operated in forward direction. Hence, the index of all parameters should be "F" instead of "Z". Connect the the cathode electrode to the negative pole

RATINGS AND CHARACTERISTIC CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)


Breakdown characteristics

$T_J = \text{constant (pulsed)}$



Breakdown characteristics

$T_J = \text{constant (pulsed)}$




RATINGS AND CHARACTERISTIC CURVES


($T_A = 25^\circ\text{C}$ unless otherwise noted)

Breakdown characteristics

$T_j = \text{constant (pulsed)}$




Forward characteristics



Admissible power dissipation versus ambient temperature

Valid provided that electrodes are kept at ambient temperature




RATINGS AND CHARACTERISTIC CURVES


($T_A = 25^\circ\text{C}$ unless otherwise noted)

Pulse thermal resistance versus pulse duration


Valid provided that the electrodes are kept at ambient temperature




Dynamic resistance versus Zener current



Capacitance versus Zener voltage




Dynamic resistance versus Zener current



RATINGS AND CHARACTERISTIC CURVES


($T_A=25^\circ\text{C}$ unless otherwise noted)

Dynamic resistance versus Zener current




Thermal differential resistance versus Zener voltage


Valid provided that electrodes are kept at ambient temperature



Dynamic resistance versus Zener voltage




Temperature dependence of Zener voltage versus Zener voltage




RATINGS AND CHARACTERISTIC CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)


Temperature dependence of Zener voltage versus Zener voltage




Change of Zener voltage versus junction temperature



Change of Zener voltage versus junction temperature



Change of Zener voltage from turn-on up to the point of thermal equilibrium versus Zener voltage



RATINGS AND CHARACTERISTIC CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Change of Zener voltage from turn-on up to the point of thermal equilibrium versus Zener voltage

