



STEIF POWER
TECHNOLOGY



SPD06065D1 650V Silicon Carbide Diode

Features

- 650-Volt Schottky Rectifier
- Shorter recovery time
- High-speed switching possible
- High-Frequency Operation
- Temperature-Independent Switching Behavior
- Extremely Fast Switching
- Positive Temperature Coefficient on VF


Benefits

- Higher safety margin against overvoltage
- Improved efficiency all load conditions
- Increased efficiency compared to Silicon Diode alternatives
- Reduction of Heat Sink Requirements
- Parallel Devices Without Thermal Runaway
- Essentially No Switching Losses

Applications

- Switch Mode Power Supplies
- Power Factor Correction
- Motor Drives
- HID Lighting

Package



Absolute Maximum Ratings

T_C = 25° C unless otherwise noted

Symbol	Parameter	SPD06065D1	Units
VRM	Repetitive Peak Reverse Voltage	650	V
VRSM	Surge Peak Reverse Voltage	650	V
VDC	DC Blocking Voltage	650	V
IF	Continuous Forward Current @T _c =25°C @T _c =135°C @T _c =150°C	19 9 6	A
IFRM	Repetitive Peak Forward Surge Current @T _C =25°C tp = 10 ms, Half Sine Wave @T _C =110°C	39 26	A
IFSM	Non-Repetitive Peak Forward Surge Current @T _C =25 °C tp= 10 ms, Half Sine Wave @T _C =110 °C	68 53	A
IFSM	Non-Repetitive Peak Forward Surge Current @T _C =25 °C, tp= 10 us, pulse	190	A
Ptot	Power Dissipation @T _c =25°C @T _c =110°C	81 35	W
T _J , T _{stg}	Operating Junction and Storage Temperature	-55 to +175	°C

Electrical Characteristics

$T_C = 25^\circ C$ unless otherwise noted

Symbol	Test Conditions	Test Conditions	Min	Typ	Max	Unit
VF	Forward Voltage	IF=6A, $T_C=25^\circ C$ IF=6A, $T_C=175^\circ C$	-	1.5 2.2	1.8 3.0	V
IR	Reverse Current	$VR=650V, T_C=25^\circ C$ $VR=650V, T_C=175^\circ C$	-	10 20	50 100	μA
QC	Total Capacitive Charge	$VR = 400V, IF = 6A$ $T_J = 25^\circ C$ $Q_c = \int_0^{V_R} C(V) dv$	-	22	-	nC
C	Total Capacitance	$VR = 0V, T_J = 25^\circ C, f = 1MHz$ $VR = 200V, T_J = 25^\circ C, f = 1MHz$ $VR = 400V, T_J = 25^\circ C, f = 1MHz$	-	329 38 28	-	pF
EC	Capacitance Stored Energy	$VR=400V$	-	4.3	-	μJ

Thermal Characteristics

Symbol	Parameter	Typ	Unit
$R_{\theta JC}$	Thermal Resistance from Junction to Case	1.85	$^\circ C/W$

Typical Characteristics




Figure 1. Forward Characteristics




Figure 2. Reverse Characteristics

Typical Characteristics




Figure 3. Capacitance vs. Reverse Voltage




Figure 4. Total Capacitance Charge vs. Reverse Voltage




Figure 5. Capacitance Stored Energy




Figure 6. Power Derating




Figure 7. Current Derating




Figure 8. Transient Thermal Impedance