



Features

- 100 Watts peak pulse power ($t_p = 8/20\mu s$)
- Tiny SOD-923 package
- Unidirectional configurations
- Protects one I/O port
- Low clamping voltage
- Low Leakage current
- ESD-immunity acc. IEC 61000-4-2 Level 4
 $\pm 8KV$ contact , $\pm 15KV$ air
- ESD Rating of Class 3 (> 16 kV) per HBM
- RoHS compliant



SOD-923



Schematic Diagram

Applications

- Cell Phone Handsets and Accessories
- MP3 player
- Portable Instrumentation
- Cordless Phones
- Digital Cameras

Absolute Maximum Ratings

($T_A=25^\circ C$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Peak Pulse Power ($T_P=8/20\mu S$)	P_{PP}	100	W
Peak Pulse Current ($t_P = 8/20\mu S$)	I_{PP}	9.8	A
Junction Temperature	T_J	-55 to +125	$^\circ C$
Storage temperature	T_{STG}	-55 to +150	$^\circ C$

Electrical Characteristics

($T_A=25^\circ C$ unless otherwise specified)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Reverse stand-off Voltage	V_{RWM}		-	-	3.3	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1mA$	5	-	-	V
Reverse Leakage Current	I_R	$V_R=3.3V$	-	-	2.5	μA
Clamping Voltage	V_C	$I_{PP}=9.8A, T_P=8/20\mu S$	-	10.4	-	V
Junction Capacitance	C_J	$V_R=0V, f=1MHz$	-	30	-	pF

Typical Characteristic Curves

Fig.1 Peak Pulse Power Rating Curve




Fig.2 Pulse Derating Curve




Fig.3 Pulse Waveform-8/20μs






Fig.4 Pulse Waveform-ESD(IEC61000-4-2)




Product Dimensions



SOD-923


Dim	mm	
	min	max
A	0.34	0.40
B	0.07	0.17
C	0.55	0.65
D	0.75	0.85
E	0.95	1.05
F	0.05	0.15
G	0.15	0.25

PAD Dimensions



Dim	mm
I	0.90
J	0.30
K	0.35

Package Information




TapeSize(W)	B1 max	D	E	F	K max	P0	P1	P2	T max	W max
8	4.55	1.55±0.05	1.75±0.1	3.5±0.05	2.4	4.0±0.1	2.0±0.05	2.0±0.05	0.6	8.3

Note:1.Unit : mm

2. A0, B0, and K0 are determined by component size. The clearance between the components and the cavity must be within 0.05mm min to 0.50 mm max. The component cannot rotate more than 10° within the determined cavity.

Marking



Order Information

Device	Package	Net Weight	Carrier	Quantity	HSF Status
SPESP3V3D923-2U	SOD-923	0.0006g	Tape & Reel	8000pcs / Reel	RoHS compliant