



Features


- DFN2010 package
- Protects up to 4-Lines operating at 5V
- R2R + Zener technology
- Low clamping voltage
- Low leakage current
- Ultra low capacitance (0.15pF typical I/O to I/O)
- ESD Protection for high-speed data lines to:
IEC 61000-4-2 ±8kV contact ±15kV air
- RoHS compliant



DFN2010



Pin Configuration



Schematic Diagram

Applications

- USB 3.0/3.1
- HDMI 1.4/2.0, Display Port 1.3, eSATA
- Unified Display Interface (UDI)
- Digital Visual Interface (DVI)
- High speed serial interfaces

Absolute Maximum Ratings ($T_A=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Junction Temperature	T_J	-55 to +125	°C
Storage Temperature	T_{STG}	-55 to +150	°C
Lead Soldering Temperature	T_L	260 (10sec.)	°C
Peak Pulse Current ($t_P = 8/20\mu\text{s}$)	I_{PP}	3	A
IEC 61000-4-2 Contact (ESD)	V_{ESD}	±8	kV
IEC 61000-4-2 Air (ESD)	V_{ESD}	±15	kV

Electrical Characteristics ($T_A=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Reverse Stand-off Voltage	V_{RWM}	-	-	-	5	V
Reverse Breakdown Voltage	V_{BR}	$I_T=1\text{mA}$	6	7.2	9.5	V
Reverse Leakage Current	I_R	$V_R=5\text{V}$	-	0.01	1	µA
Clamping Voltage (IEC 61000-4-5)	V_C	$I_{PP}=3\text{A}, T_P=8/20\mu\text{s}$	-	10	-	V
Trigger Voltage (IEC 61000-4-2)	V_T	$V_{ESD}=8\text{kV}$	-	135	-	V
Clamping Voltage (IEC 61000-4-2)	V_C	$V_{ESD}=8\text{kV}$	-	20	-	V
Junction Capacitance	C_J	$V_R=0\text{V}, f=1\text{MHz}, \text{I/O to I/O}$	-	0.15	-	pF
	C_J	$V_R=0\text{V}, f=1\text{MHz}, \text{I/O to GND}$	-	0.35	-	pF

Typical Characteristic Curves

Fig.1 Pulse Waveform-ESD(IEC61000-4-2)




Fig.2 IEC61000-4-2 +8kV Contact ESD Clamping Waveform




Fig.3 Eye Diagram - USB3.1 at 10Gbps per channel (with SPESUC5VD2010-5U)








Fig.4 Insertion Loss S21 - I/O to I/O



Product Dimensions

DFN2010



Dim	Millimeters		
	Min	Nom	Max
A	0.45	0.50	0.55
A1	0.00	0.02	0.05
b	0.15	0.20	0.25
D	1.95	2.00	2.05
E	0.95	1.00	1.05
e	0.40 BSC		
e1	0.80 BSC		
L	0.25	0.30	0.35
N	5		

Marking



Order Information

Device	Package	Carrier	Quantity	HSF Status
SPESUC5VD2010-5U	DFN2010	Tape & Reel (7")	3000pcs / Reel	RoHS Compliant