




STEIFPOWER
TECHNOLOGY

LS36A

Surface Mount Schottky Rectifier
Reverse Voltage 60V Forward Current 3A

Features

- Low forward voltage drop
- Low leakage current
- Moisture sensitivity: level 1, per J-STD-020
- Low profile, typical thickness 1.0mm
- Solder dip 260 °C, 10 s



Package: eSGB(SMAF)

Applications

For uses in low voltage, high frequency inverters, free wheeling and polarity protection applications.

Maximum Ratings ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	LS36A	Unit
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	60	V
Maximum RMS Voltage	V _{RMS}	42	V
Maximum DC Blocking Voltage	V _{DC}	60	V
Maximum Average Forward Rectified Current	I _{F(AV)}	3.0	A
Peak Forward Surge Current (8.3 ms single half sine-wave superimposed on rated load)	I _{FSM}	100	A
Operating Junction and Storage Temperature Range	T _J , T _{STG}	-55 to +150	°C

Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
Instantaneous Forward Voltage	I _F =1A, T _A =25°C	V _F	-	0.48	0.60	V
	I _F =3A, T _A =25°C		-	0.67	0.75	
	I _F =3A, T _A =125°C		-	0.59	-	
Maximum DC Reverse Current @ rated DC Blocking Voltage	T _A =25°C	I _R	0.3			mA
	T _A =125°C		30			
Typical Junction Capacitance	4.0 V, 1 MHz	C _J	94			pF
Typical Thermal Resistance	Junction to Mount	R _{θJM} ¹⁾	20			°C/W

Note 1) Mounted on PCB with 8.0x8.0mm copper pads, 2 OZ, FR4 PCB.



STEIFPOWER
TECHNOLOGY

LS36A

Surface Mount Schottky Rectifier
Reverse Voltage 60V Forward Current 3A

Ratings and Characteristics Curves ($T_A = 25^\circ C$ unless otherwise noted)




Figure 1. Typical Instantaneous Forward Characteristics




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current




Figure 3. Typical Reverse Characteristics




Figure 4. Typical Junction Capacitance




Figure 5. Forward Current Derating Curve




STEIFPOWER
TECHNOLOGY

LS36A

Surface Mount Schottky Rectifier
Reverse Voltage 60V Forward Current 3A


Package Outline Dimensions

eSGB (SMAF)



DIM	Unit: mm		Unit: inch	
	MIN	MAX	MIN	MAX
A	0.92	1.08	0.036	0.043
A1	0	0.1	0.000	0.004
B	1.25	1.45	0.049	0.057
C	0.1	0.25	0.004	0.010
D	2.6	2.8	0.102	0.110
E	4.1	4.3	0.161	0.169
L	0.7	1.1	0.028	0.043
HE	4.8	5.2	0.189	0.205

Soldering footprint



Packing Information

Packing quantities

3000 pcs/Reel , 12mm Tape, 13" Reel

Tape & Reel Specification

