



STEIF POWER
TECHNOLOGY

20V P-Channel Dual MOSFETs

SPC2209V

General Description


These P-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for high efficiency fast switching applications.

BVDSS	RDS(ON)	ID
-20V	33mΩ	-7.5A

Features

- -20V, -7.5A, RDS(ON) = 33mΩ @ VGS = -4.5V
- Improved dv/dt capability
- Fast switching
- Green Device Available

PPAK3x3 Dual Pin Configuration



Applications

- MB / VGA / Vcore
- POL Applications
- Networking



Absolute Maximum Ratings $T_c=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	-20	V
V_{GS}	Gate-Source Voltage	± 10	V
I_D	Drain Current – Continuous ($T_c=25^\circ\text{C}$)	-7.5	A
	Drain Current – Continuous ($T_c=100^\circ\text{C}$)	-4.5	A
I_{DM}	Drain Current – Pulsed ¹	-30	A
P_D	Power Dissipation ($T_c=25^\circ\text{C}$)	25	W
	Power Dissipation – Derate above 25°C	0.2	W/°C
T_{STG}	Storage Temperature Range	-55 to 150	°C
T_J	Operating Junction Temperature Range	-55 to 150	°C

Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JA}$	Thermal Resistance Junction to ambient	---	62	°C/W
$R_{\theta JC}$	Thermal Resistance Junction to Case	---	5	°C/W

Electrical Characteristics ($T_J=25^\circ\text{C}$, unless otherwise noted)

Off Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{\text{GS}}=0\text{V}$, $I_D=-250\mu\text{A}$	-20	---	---	V
$\Delta \text{BV}_{\text{DSS}}/\Delta T_J$	BV_{DSS} Temperature Coefficient	Reference to 25°C , $I_D=-1\text{mA}$	---	-0.02	---	$\text{V}/^\circ\text{C}$
I_{DSS}	Drain-Source Leakage Current	$V_{\text{DS}}=-20\text{V}$, $V_{\text{GS}}=0\text{V}$, $T_J=25^\circ\text{C}$	---	---	-1	μA
		$V_{\text{DS}}=-16\text{V}$, $V_{\text{GS}}=0\text{V}$, $T_J=125^\circ\text{C}$	---	---	-10	μA
I_{GSS}	Gate-Source Leakage Current	$V_{\text{GS}}=\pm 10\text{V}$, $V_{\text{DS}}=0\text{V}$	---	---	± 100	nA

On Characteristics

$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance ²	$V_{\text{GS}}=-4.5\text{V}$, $I_D=-4\text{A}$	---	28	33	$\text{m}\Omega$	
		$V_{\text{GS}}=-2.5\text{V}$, $I_D=-3\text{A}$	---	37	45	$\text{m}\Omega$	
		$V_{\text{GS}}=-1.8\text{V}$, $I_D=-2\text{A}$	---	49	65	$\text{m}\Omega$	
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{\text{GS}}=V_{\text{DS}}$, $I_D = -250\mu\text{A}$		-0.3	-0.6	-1	V
$\Delta V_{\text{GS(th)}}$	$V_{\text{GS(th)}}$ Temperature Coefficient			---	2	---	$\text{mV}/^\circ\text{C}$
g_{fs}	Forward Transconductance	$V_{\text{DS}}=-10\text{V}$, $I_D=-3\text{A}$	---	8.5	---	S	

Dynamic and switching Characteristics

Q_g	Total Gate Charge ^{2,3}	$V_{\text{DS}}=-10\text{V}$, $V_{\text{GS}}=-4.5\text{V}$, $I_D=-4\text{A}$	---	16.1	25	nC
Q_{gs}	Gate-Source Charge ^{2,3}		---	1.8	3.6	
Q_{gd}	Gate-Drain Charge ^{2,3}		---	3.8	7	
$T_{\text{d(on)}}$	Turn-On Delay Time ^{2,3}	$V_{\text{DD}}=-10\text{V}$, $V_{\text{GS}}=-4.5\text{V}$, $R_G=25\Omega$ $I_D=1\text{A}$	---	8.2	16	ns
T_r	Rise Time ^{2,3}		---	30	57	
$T_{\text{d(off)}}$	Turn-Off Delay Time ^{2,3}		---	71	135	
T_f	Fall Time ^{2,3}		---	20	38	
C_{iss}	Input Capacitance	$V_{\text{DS}}=-15\text{V}$, $V_{\text{GS}}=0\text{V}$, $F=1\text{MHz}$	---	1440	2100	pF
C_{oss}	Output Capacitance		---	155	230	
C_{rss}	Reverse Transfer Capacitance		---	115	170	

Drain-Source Diode Characteristics and Maximum Ratings

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I_s	Continuous Source Current	$V_G=V_D=0\text{V}$, Force Current	---	---	-7.5	A
I_{SM}	Pulsed Source Current ²		---	---	-15	A
V_{SD}	Diode Forward Voltage ²	$V_{\text{GS}}=0\text{V}$, $I_s=-1\text{A}$, $T_J=25^\circ\text{C}$	---	---	-1	V
t_{rr}	Reverse Recovery Time	$V_{\text{GS}}=0\text{V}$, $I_s=-1\text{A}$, $di/dt=-100\text{A}/\mu\text{s}$	---	---	---	ns
Q_{rr}	Reverse Recovery Charge	$T_J=25^\circ\text{C}$	---	---	---	nC

Note :

- Repetitive Rating : Pulsed width limited by maximum junction temperature.
- The data tested by pulsed , pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2\%$.
- Essentially independent of operating temperature.



STEIF POWER
TECHNOLOGY

20V P-Channel Dual MOSFETs

SPC2209V




Fig.1 Continuous Drain Current vs. T_C




Fig.2 Normalized RD_{SON} vs. T_J




Fig.3 Normalized V_{th} vs. T_J




Fig.4 Gate Charge Waveform




Fig.5 Normalized Transient Response




Fig.6 Maximum Safe Operation Area




Fig.7 Switching Time Waveform





Fig.8 Gate Charge Waveform



PPAK3x3 Dual PACKAGE INFORMATION



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.700	0.800	0.028	0.031
b	0.250	0.350	0.010	0.013
c	0.100	0.250	0.004	0.009
D	3.250	3.450	0.128	0.135
D1	3.000	3.200	0.119	0.125
D2	1.780	1.980	0.070	0.077
D3	0.130 REF		0.005 REF	
E	3.200	3.400	0.126	0.133
E1	3.000	3.200	0.119	0.125
E2	2.390	2.590	0.094	0.102
e	0.650 BSC		0.026 BSC	
H	0.300	0.500	0.011	0.019
L	0.300	0.500	0.011	0.019
L1	0.130 REF		0.005 REF	
K	0.300 REF		0.012 REF	
θ	0°	12°	0°	12°
M	0.150 REF		0.006 REF	