


### General Description

These N+P dual Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for high efficiency fast switching applications.

BVDSS	RDSON	ID
60V	30mΩ	19A
-60V	48mΩ	-17A

### TO252-4L Pin Configuration



### Features

- Fast switching
- Green Device Available
- Suit for 4.5V Gate Drive Applications

### Applications

- DC Fan
- Motor Drive Applications
- Networking
- Half / Full Bridge Topology



### Absolute Maximum Ratings $T_c=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Rating		Units
$V_{DS}$	Drain-Source Voltage	60	-60	V
$V_{GS}$	Gate-Source Voltage	$\pm 20$	$\pm 20$	V
$I_D$	Drain Current – Continuous ( $T_c=25^\circ\text{C}$ )	19	17	A
	Drain Current – Continuous ( $T_c=100^\circ\text{C}$ )	12	10.7	A
$I_{DM}$	Drain Current – Pulsed <sup>1</sup>	76	68	A
EAS	Single Pulse Avalanche Energy <sup>2</sup>	26.4	54.4	mJ
IAS	Single Pulse Avalanche Current <sup>2</sup>	23	33	A
$P_D$	Power Dissipation ( $T_c=25^\circ\text{C}$ )	20.1		W
	Power Dissipation – Derate above $25^\circ\text{C}$	0.16		W/ $^\circ\text{C}$
$T_{STG}$	Storage Temperature Range	-55 to 150		$^\circ\text{C}$
$T_J$	Operating Junction Temperature Range	-55 to 150		$^\circ\text{C}$

### Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JC}$	Thermal Resistance Junction to Case	---	6.2	$^\circ\text{C}/\text{W}$
$R_{\theta JA}$	Thermal Resistance Junction to Ambient	---	62	$^\circ\text{C}/\text{W}$

## N-CH Electrical Characteristics (T<sub>J</sub>=25 °C, unless otherwise)

### Off Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV <sub>DSS</sub>	Drain-Source Breakdown Voltage	V <sub>GS</sub> =0V, I <sub>D</sub> =250uA	60	---	---	V
ΔBV <sub>DSS</sub> /ΔT <sub>J</sub>	BV <sub>DSS</sub> Temperature Coefficient	Reference to 25°C, I <sub>D</sub> =1mA	---	0.07	---	V/°C
I <sub>DSS</sub>	Drain-Source Leakage Current	V <sub>DS</sub> =60V, V <sub>GS</sub> =0V, T <sub>J</sub> =25°C	---	---	1	uA
		V <sub>DS</sub> =48V, V <sub>GS</sub> =0V, T <sub>J</sub> =125°C	---	---	10	uA
I <sub>GSS</sub>	Gate-Source Leakage Current	V <sub>GS</sub> =±20V, V <sub>DS</sub> =0V	---	---	±100	nA

### On Characteristics

R <sub>DS(ON)</sub>	Static Drain-Source On-Resistance	V <sub>GS</sub> =10V, I <sub>D</sub> =15A	---	25	30	mΩ
		V <sub>GS</sub> =4.5V, I <sub>D</sub> =10A	---	28	36	mΩ
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>GS</sub> =V <sub>DS</sub> , I <sub>D</sub> =250uA	1.2	1.6	2.5	V
ΔV <sub>GS(th)</sub>	V <sub>GS(th)</sub> Temperature Coefficient		---	-4.6	---	mV/°C
gfs	Forward Transconductance	V <sub>DS</sub> =10V, I <sub>D</sub> =3A	---	10	---	S

### Dynamic and switching Characteristics


Q <sub>g</sub>	Total Gate Charge <sup>3, 4</sup>	V <sub>DS</sub> =30V, V <sub>GS</sub> =10V, I <sub>D</sub> =10A	---	16.6	24	nC
Q <sub>gs</sub>	Gate-Source Charge <sup>3, 4</sup>		---	2.2	4.4	
Q <sub>gd</sub>	Gate-Drain Charge <sup>3, 4</sup>		---	3.9	8	
T <sub>d(on)</sub>	Turn-On Delay Time <sup>3, 4</sup>	V <sub>DD</sub> =30V, V <sub>GS</sub> =10V, R <sub>G</sub> =6Ω I <sub>D</sub> =1A	---	4.6	9	ns
T <sub>r</sub>	Rise Time <sup>3, 4</sup>		---	14.8	28	
T <sub>d(off)</sub>	Turn-Off Delay Time <sup>3, 4</sup>		---	27.2	52	
T <sub>f</sub>	Fall Time <sup>3, 4</sup>		---	7.8	15	
C <sub>iss</sub>	Input Capacitance	V <sub>DS</sub> =30V, V <sub>GS</sub> =0V, F=1MHz	---	1180	1720	pF
C <sub>oss</sub>	Output Capacitance		---	68	100	
C <sub>rss</sub>	Reverse Transfer Capacitance		---	45	70	
R <sub>g</sub>	Gate resistance	V <sub>GS</sub> =0V, V <sub>DS</sub> =0V, F=1MHz	---	2.1	4.2	Ω

### Drain-Source Diode Characteristics and Maximum Ratings


Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I <sub>S</sub>	Continuous Source Current	V <sub>G</sub> =V <sub>D</sub> =0V, Force Current	---	---	19	A
I <sub>SM</sub>	Pulsed Source Current		---	---	38	A
V <sub>SD</sub>	Diode Forward Voltage	V <sub>GS</sub> =0V, I <sub>S</sub> =1A, T <sub>J</sub> =25°C	---	---	1	V

Note :


1. Repetitive Rating : Pulsed width limited by maximum junction temperature.
2. V<sub>DD</sub>=25V, V<sub>GS</sub>=10V, L=0.1mH, N-CH I<sub>AS</sub>=23A., P-CH I<sub>AS</sub>=33A, R<sub>G</sub>=25Ω, Starting T<sub>J</sub>=25°C.
3. The data tested by pulsed, pulse width ≤ 300us, duty cycle ≤ 2%.
4. Essentially independent of operating temperature.




**Fig.1 Continuous Drain Current vs.  $T_c$**




**Fig.2 Normalized  $R_{DS(on)}$  vs.  $T_j$**




**Fig.3 Normalized  $V_{th}$  vs.  $T_j$**



**Fig.4 Gate Charge Waveform**



**Fig.5 Normalized Transient Impedance**



**Fig.6 Maximum Safe Operation Area**

## P-CH Electrical Characteristics (T<sub>J</sub>=25 °C, unless otherwise

### Off Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV <sub>DSS</sub>	Drain-Source Breakdown Voltage	V <sub>GS</sub> =0V, I <sub>D</sub> =-250uA	-60	---	---	V
ΔBV <sub>DSS</sub> /ΔT <sub>J</sub>	BV <sub>DSS</sub> Temperature Coefficient	Reference to 25°C, I <sub>D</sub> =-1mA	---	-0.05	---	V/°C
I <sub>DSS</sub>	Drain-Source Leakage Current	V <sub>DS</sub> =-60V, V <sub>GS</sub> =0V, T <sub>J</sub> =25°C	---	---	-1	uA
		V <sub>DS</sub> =-48V, V <sub>GS</sub> =0V, T <sub>J</sub> =125°C	---	---	-10	uA
I <sub>GSS</sub>	Gate-Source Leakage Current	V <sub>GS</sub> =±20V, V <sub>DS</sub> =0V	---	---	±100	nA

### On Characteristics

R <sub>DS(ON)</sub>	Static Drain-Source On-Resistance	V <sub>GS</sub> =-10V, I <sub>D</sub> =-15A	---	40	48	mΩ
		V <sub>GS</sub> =-4.5V, I <sub>D</sub> =-10A	---	53	68	mΩ
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>GS</sub> =V <sub>DS</sub> , I <sub>D</sub> =-250uA	-1.2	-1.6	-2.5	V
ΔV <sub>GS(th)</sub>	V <sub>GS(th)</sub> Temperature Coefficient		---	5	---	mV/°C
gfs	Forward Transconductance	V <sub>DS</sub> =-10V, I <sub>D</sub> =-3A	---	10	---	S

### Dynamic and switching Characteristics


Q <sub>g</sub>	Total Gate Charge <sup>2,3</sup>	V <sub>DS</sub> =-30V, V <sub>GS</sub> =-10V, I <sub>D</sub> =-8A	---	22.4	31	nC
Q <sub>gs</sub>	Gate-Source Charge <sup>2,3</sup>		---	4.1	6	
Q <sub>gd</sub>	Gate-Drain Charge <sup>2,3</sup>		---	5.2	7	
T <sub>d(on)</sub>	Turn-On Delay Time <sup>2,3</sup>	V <sub>DD</sub> =-30V, V <sub>GS</sub> =-10V, R <sub>G</sub> =6Ω I <sub>D</sub> =-1A	---	13	25	ns
T <sub>r</sub>	Rise Time <sup>2,3</sup>		---	42.4	81	
T <sub>d(off)</sub>	Turn-Off Delay Time <sup>2,3</sup>		---	64.6	123	
T <sub>f</sub>	Fall Time <sup>2,3</sup>		---	16.4	31	
C <sub>iss</sub>	Input Capacitance	V <sub>DS</sub> =-30V, V <sub>GS</sub> =0V, F=1MHz	---	1250	1810	pF
C <sub>oss</sub>	Output Capacitance		---	85	125	
C <sub>rss</sub>	Reverse Transfer Capacitance		---	65	95	
R <sub>g</sub>	Gate resistance		V <sub>GS</sub> =0V, V <sub>DS</sub> =0V, F=1MHz		15	

### Drain-Source Diode Characteristics and Maximum Ratings


Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I <sub>S</sub>	Continuous Source Current	V <sub>G</sub> =V <sub>D</sub> =0V, Force Current	---	---	-17	A
I <sub>SM</sub>	Pulsed Source Current		---	---	-34	A
V <sub>SD</sub>	Diode Forward Voltage	V <sub>GS</sub> =0V, I <sub>S</sub> =-1A, T <sub>J</sub> =25°C	---	---	-1	V

Note :


5. Repetitive Rating : Pulsed width limited by maximum junction temperature.
6. The data tested by pulsed, pulse width ≤ 300us, duty cycle ≤ 2%.
7. Essentially independent of operating temperature.




**Fig.7 Continuous Drain Current vs.  $T_c$**




**Fig.8 Normalized  $R_{DS(on)}$  vs.  $T_j$**




**Fig.9 Normalized  $V_{th}$  vs.  $T_j$**



**Fig.10 Gate Charge Waveform**




**Fig.11 Normalized Transient Impedance**



**Fig.12 Maximum Safe Operation Area**

## TO252-4L PACKAGE INFORMATION



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MAX	MIN	MAX	MIN
A	2.400	2.200	0.094	0.087
A1	0.150	0.000	0.006	0.000
B	0.600	0.400	0.024	0.016
b2	0.800	0.500	0.031	0.020
b3	5.500	5.200	0.217	0.205
C	0.508typ.		0.02typ.	
c2	0.550	0.450	0.022	0.018
D	5.800	5.400	0.228	0.213
D1	---	4.570	---	0.180
E	6.800	6.400	0.268	0.252
E1	---	3.810	---	0.150
E	1.27ref.		0.05ref.	
F	0.600	0.400	0.024	0.016
H	10.200	9.400	0.402	0.370
L	1.770	1.400	0.070	0.055
L1	3.000	2.400	0.118	0.094
L4	1.200	0.800	0.047	0.031