



General Description

These P-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for high efficiency fast switching applications.

TO252 Pin Configuration



BVDSS	RDS(ON)	ID
-60V	48mΩ	-16A

Features

- -60V, -16A, RDS(ON) = 48mΩ@VGS = -10V
- Improved dv/dt capability
- Fast switching
- 100% EAS Guaranteed
- Green Device Available

Applications

- Motor Drive
- Power Tools
- LED Lighting



Absolute Maximum Ratings T_c=25°C unless otherwise noted

Symbol	Parameter	Rating	Units
V _{DS}	Drain-Source Voltage	-60	V
V _{Gs}	Gate-Source Voltage	±20	V
I _D	Drain Current – Continuous (T _c =25°C)	-16	A
	Drain Current – Continuous (T _c =100°C)	-10	A
I _{DM}	Drain Current – Pulsed ¹	-64	A
EAS	Single Pulse Avalanche Energy ²	51	mJ
I _{AS}	Single Pulse Avalanche Current ²	-32	A
P _D	Power Dissipation (T _c =25°C)	25	W
	Power Dissipation – Derate above 25°C	0.2	W/°C
T _{STG}	Storage Temperature Range	-50 to 150	°C
T _J	Operating Junction Temperature Range	-50 to 150	°C

Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Unit
R _{θJA}	Thermal Resistance Junction to ambient	---	62	°C/W
R _{θJC}	Thermal Resistance Junction to Case	---	5	°C/W

Electrical Characteristics (T_J=25 °C, unless otherwise noted)
Off Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V , I _D =-250uA	-60	---	---	V
△BV _{DSS} /△T _J	BV _{DSS} Temperature Coefficient	Reference to 25°C , I _D =-1mA	---	-0.05	---	V/°C
I _{DSS}	Drain-Source Leakage Current	V _{DS} =-60V , V _{GS} =0V , T _J =25°C	---	---	-1	uA
		V _{DS} =-48V , V _{GS} =0V , T _J =125°C	---	---	-10	uA
I _{GSS}	Gate-Source Leakage Current	V _{GS} =±20V , V _{DS} =0V	---	---	±100	nA

On Characteristics

R _{DSON}	Static Drain-Source On-Resistance	V _{GS} =-10V , I _D =-8A	---	39	48	mΩ
		V _{GS} =-4.5V , I _D =-4A	---	53	65	mΩ
V _{GS(th)}	Gate Threshold Voltage	V _{GS} =V _{DS} , I _D =-250uA	-1.2	-1.6	-2.2	V
△V _{GS(th)}	V _{GS(th)} Temperature Coefficient		---	5	---	mV/°C
g _{fS}	Forward Transconductance	V _{DS} =-10V , I _D =-8A	---	10	---	S

Dynamic and switching Characteristics

Q _g	Total Gate Charge ^{3, 4}	V _{DS} =-30V , V _{GS} =-10V , I _D =-8A	---	22.4	31	nC
Q _{gs}	Gate-Source Charge ^{3, 4}		---	4.1	6	
Q _{gd}	Gate-Drain Charge ^{3, 4}		---	5.2	7	
T _{d(on)}	Turn-On Delay Time ^{3, 4}	V _{DD} =-30V , V _{GS} =-10V , R _G =6Ω	---	13	25	ns
T _r	Rise Time ^{3, 4}		---	42.4	81	
T _{d(off)}	Turn-Off Delay Time ^{3, 4}		---	64.6	123	
T _f	Fall Time ^{3, 4}		---	16.4	31	
C _{iss}	Input Capacitance	V _{DS} =-30V , V _{GS} =0V , F=1MHz	---	1250	1810	pF
C _{oss}	Output Capacitance		---	85	125	
C _{rss}	Reverse Transfer Capacitance		---	65	95	
R _g	Gate resistance	V _{GS} =0V , V _{DS} =0V , F=1MHz	---	15	30	Ω

Drain-Source Diode Characteristics and Maximum Ratings

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I _S	Continuous Source Current	V _G =V _D =0V , Force Current	---	---	-16	A
I _{SM}	Pulsed Source Current		---	---	-64	A
V _{SD}	Diode Forward Voltage	V _{GS} =0V , I _S =-1A , T _J =25°C	---	---	-1	V
t _{rr}	Reverse Recovery Time ³	V _{GS} =0V , I _S =-1A , dI/dt=100A/μs	---	---	---	ns
Q _{rr}	Reverse Recovery Charge ³		---	---	---	nC

Note :

1. Repetitive Rating : Pulsed width limited by maximum junction temperature.
2. V_{DD}=-25V,V_{GS}=-10V,L=0.1mH,I_{AS}=-32A.,R_G=25Ω, Starting T_J=25°C
3. The data tested by pulsed , pulse width ≤ 300us , duty cycle ≤ 2%.
4. Essentially independent of operating temperature.




Fig.1 Continuous Drain Current vs. T_C




Fig.2 Normalized RD_{SON} vs. T_J




Fig.3 Normalized V_{th} vs. T_J




Fig.4 Gate Charge Waveform




Fig.5 Typical Output Characteristics




Fig.6 Turn-On Resistance vs. I_D




Fig.7 Capacitance Characteristics




Fig.8 Normalized Transient Impedance




Fig.9 Maximum Safe Operation Area




Fig.10 Switching Time Waveform





Fig.11 EAS Waveform



TO252 PACKAGE INFORMATION



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	2.20	2.40	0.087	0.094
A1	0.91	1.11	0.036	0.044
A2	0.00	0.15	0.000	0.006
B	6.50	6.70	0.256	0.264
C	0.46	0.580	0.018	0.230
C1	0.46	0.580	0.018	0.030
D	5.10	5.46	0.201	0.215
E	2.186	2.386	0.086	0.094
F	0.74	0.94	0.029	0.037
F1	0.660	0.860	0.026	0.034
L	9.80	10.40	0.386	0.409
L1	2.9REF		0.114REF	
L2	6.00	6.20	0.236	0.244
L3	0.60	1.00	0.024	0.039
θ	3°	9°	3°	9°

RECOMMEND FOOTPRINT INFORMATION

