


General Description

These N-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for high efficiency fast switching applications.

TO220 Pin Configuration



Absolute Maximum Ratings $T_c=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	65	V
V_{GS}	Gate-Source Voltage	+20/-12	V
I_D	Drain Current – Continuous ($T_c=25^\circ\text{C}$)	180	A
	Drain Current – Continuous ($T_c=100^\circ\text{C}$)	113	A
I_{DM}	Drain Current – Pulsed ¹	720	A
EAS	Single Pulse Avalanche Energy ²	500	mJ
IAS	Single Pulse Avalanche Current ²	100	A
P_D	Power Dissipation ($T_c=25^\circ\text{C}$)	278	W
	Power Dissipation – Derate above 25°C	2.22	W/ $^\circ\text{C}$
T_{STG}	Storage Temperature Range	-50 to 150	$^\circ\text{C}$
T_J	Operating Junction Temperature Range	-50 to 150	$^\circ\text{C}$

Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JA}$	Thermal Resistance Junction to ambient	---	62	$^\circ\text{C}/\text{W}$
$R_{\theta JC}$	Thermal Resistance Junction to Case	---	0.45	$^\circ\text{C}/\text{W}$

BVDSS	RDSON	ID
65V	2.2mΩ	180A

Features

- 65V, 180A, $R_{DS(ON)} = 2.2\text{m}\Omega @ V_{GS} = 10\text{V}$
- Improved dv/dt capability
- Fast switching
- 100% EAS Guaranteed
- Green Device Available

Applications

- Networking
- Load Switch
- LED applications
- Quick Charger



Electrical Characteristics (T_J=25 °C, unless otherwise noted)
Off Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V , I _D =250uA	65	---	---	V
△BV _{DSS} /△T _J	BV _{DSS} Temperature Coefficient	Reference to 25°C , I _D =1mA	---	0.024	---	V/°C
I _{DSS}	Drain-Source Leakage Current	V _{DS} =60V , V _{GS} =0V , T _J =25°C	---	---	1	uA
		V _{DS} =48V , V _{GS} =0V , T _J =85°C	---	---	10	uA
I _{GSS}	Gate-Source Leakage Current	V _{GS} =20V , V _{DS} =0V	---	---	100	nA

On Characteristics

R _{DSON}	Static Drain-Source On-Resistance	V _{GS} =10V , I _D =20A	---	1.7	2.2	mΩ
		V _{GS} =4.5V , I _D =15A	---	2.8	3.7	mΩ
V _{GS(th)}	Gate Threshold Voltage	V _{GS} =V _{DS} , I _D =250uA	1	1.5	2.5	V
△V _{GS(th)}	V _{GS(th)} Temperature Coefficient		---	-5.7	---	mV/°C
gfs	Forward Transconductance	V _{DS} =10V , I _D =3A	---	18	---	S

Dynamic and switching Characteristics

Q _g	Total Gate Charge ^{3, 4}	V _{DS} =52V , V _{GS} =10V , I _D =10A	---	130	260	nC
Q _{gs}	Gate-Source Charge ^{3, 4}		---	15.4	31	
Q _{gd}	Gate-Drain Charge ^{3, 4}		---	35	70	
T _{d(on)}	Turn-On Delay Time ^{3, 4}	V _{DD} =30V , V _{GS} =10V , R _G =6Ω	---	37	74	ns
T _r	Rise Time ^{3, 4}		---	11.5	23	
T _{d(off)}	Turn-Off Delay Time ^{3, 4}		---	31	62	
T _f	Fall Time ^{3, 4}		---	10	20	
C _{iss}	Input Capacitance	V _{DS} =25V , V _{GS} =0V , F=1MHz	---	9040	18000	pF
C _{oss}	Output Capacitance		---	2180	4360	
C _{rss}	Reverse Transfer Capacitance		---	318	636	
R _g	Gate resistance	V _{GS} =0V, V _{DS} =0V, F=1MHz	---	2.16	---	Ω

Drain-Source Diode Characteristics and Maximum Ratings

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I _S	Continuous Source Current	V _G =V _D =0V , Force Current	---	---	180	A
I _{SM}	Pulsed Source Current		---	---	360	A
V _{SD}	Diode Forward Voltage	V _{GS} =0V , I _S =1A , T _J =25°C	---	---	1	V

Note :

1. Repetitive Rating : Pulsed width limited by maximum junction temperature.
2. V_{DD}=25V,V_{GS}=10V,L=0.1mH,I_{AS}=100A.,R_G=25Ω, Starting T_J=25°C.
3. The data tested by pulsed , pulse width ≤ 300us , duty cycle ≤ 2%.
4. Essentially independent of operating temperature.




Fig.1 Continuous Drain Current vs. T_C




Fig.2 Normalized $R_{DS(on)}$ vs. T_J




Fig.3 Normalized V_{th} vs. T_J




Fig.4 Gate Charge Characteristics




Fig.5 Normalized Transient Impedance




Fig.6 Maximum Safe Operation Area




Fig.7 Switching Time Waveform





Fig.8 Gate Charge Waveform

TO220 PACKAGE INFORMATION



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MAX	MIN	MAX	MIN
A	10.300	9.700	0.406	0.382
A1	8.840	8.440	0.348	0.332
A2	1.250	1.050	0.049	0.041
A3	5.300	5.100	0.209	0.201
B	16.200	15.400	0.638	0.606
C	4.680	4.280	0.184	0.169
C1	1.500	1.100	0.059	0.043
D	1.000	0.600	0.039	0.024
E	3.800	3.400	0.150	0.134
G	9.300	8.700	0.366	0.343
H	0.600	0.400	0.024	0.016
K	2.700	2.100	0.106	0.083
L	13.600	12.800	0.535	0.504
M	1.500	1.100	0.059	0.043
N	2.590	2.490	0.102	0.098
T	W0.35		W0.014	
DIA	Φ1.5 TYP.	deep0.2 TYP.	Φ0.059 TYP.	deep0.008 TYP.